

Champion CTL 550 SS Pneumatic thermal laminator machine with automatic sheet separator



Special Features:

- Pneumatic pressure for easy and quick adjustment of laminating pressure.
- Large diameter laminating cylinder for efficient and high quality lamination.
- No sheet detection and tripping
- Japanese made programmable digital temperature control for consistent laminating heat.
- Bottom pressure roller coated with special non sticky industrial rubber.
- Film slitting unit with imported slitting blade.
- Film perforating unit for easy sheet separation.
- Advanced resistor based heating system
- Efficient sheet separation system with specially designed rollers.
- Siemens simatic panel with PLC for easy control all functions

Technical Specification:

Max. Working width : 550 mm

Max. Paper Size : 520 mm X 720 mm
Min. Paper Size : 210 mm X 300 mm
Max. feed speed m/min : 20 mtrs / min
Paper Thickness : 120 -350 gsm

Total Power : 7.7 Kw

Voltage : 220V / 380V 50 HZ Air requirement : 2 cfm 100 psi 0.25

Laminating Temperature : 70 -130

Dimension of Machine : 2800 X 980 X 1570 mm

Weight : 600 Kg





INDIA: Rediands Machinery Pvt. Ltd, P. B 102, Thrissur- 1, Kerala, India, Ph: +91 487 329 0309, Fax: +91 487 2320951 sales@rediandsmpl.com KINGDOM OF SAUDI ARABIA: Afra East Trading Est., Al Faisalia, Riyadh KSA. Tel: +96612423644, sales@afraprintequip.com KENYA: Afra International FZC, PO Box: 99-00507, Viwandani, Suite: 11-B, 3rd Floor, Vision Plaza, Mombasa Road, Nairobi- Kenya, Tel: +254202691917 / 2691918, Fax: +254202678132 NIGERIA: Afra International FZC, No: 10 Dillion Street, Kirikiri, Apapa, Lagos, Tel: +2348133571848 CHINA: Shanghal Aslanray Industry Development Co. Ltd., Jintai Bidg No 1398, Jinqiao Road, Pudong, Shanghai 201206, P.R. China, Shanghai Loretta Machinery Manufacturing Co. Ltd., 5th Building, No 188 Lane 4788, Baoan Road, Jiading, Shanghai, P.R. China, Ph: +86 21 50756992, Fax: +86 21 50756995, E-mail: sales@asl.net.cn

sales@afraprintequip.com, www.afraprintequip.com

Ph: +9714 2672 448 / 2670 242, Fax: +9714 2672 449 / 2670 582